KV-S2025C WorkGroup Color Scanner

The KV-S2025C is a duplex full color desktop scanner that is an ideal scanning system in today's business environment. Compact and lightweight, the KV-S2025C offers a powerful feature set that you would find on more expensive scanners. Equipped with Panasonic Image Enhancement Technology, the KV-S2025C is a versatile binary and color scanner which capture your documents at 24 ppm / 42 ipm in binary, 10 ppm / 18 ipm in color, and up to 600 dpi optical resolution, making your workgroup scanning worries a thing of the past.



- Full Color Duplex Production Scanning at 10 ppm / 18 ipm (Letter, Portrait 150 dpi)
- Panasonic Image Enhancement Technology (PIE)
- PaperPort SE software
- Reliable Throughput Image Viewer image capture utility included
- R, G, B color drop-out capability
- ISIS® Certified and TWAIN Compliant drivers standard
- Kofax Certified
- 100 dpi -600 dpi Color / Binary
- SCSI III

Scanning Face: Duplex Scanning

Scanning Method: Front: Three-line (R, G, B) CIS Back: Three-line (R, G, B) CIS

Scanning Speed: B/W 24 ppm Simplex (Letter, Portrait, 200 dpi)

B/W 42 ipm Duplex (Letter, Portrait, 200 dpi)
Color 10 ppm Simplex (Letter, Portrait, 150 dpi)
Color 18 ipm Duplex (Letter, Portrait, 150 dpi)

Scanning Resolution: 100 dpi -600 dpi Monochrome/Color scanning; Optical resolution

Paper Size:

Business card 2.0" x 2.8" to legal 8.5" x 14"

Continuous feed up to 25" (single sheet)

Paper Thickness:

Single Paper Feed:

Continuous Paper Feed:

2.0 to 5.9 mils (1 mil = 1/1000 inch)

2.36 to 5.9 mils (1 mil = 1/1000 inch)

Paper Weight:

Single Paper Feed: 10.7 to 33.9 lbs (37.50 to 127.125 g/m²)
Continuous Paper Feed: 13.3 to 33.9 lbs (49.875 to 127.125 g/m²)

Auto Document Feeder: 100 pages (20 lbs.)

Length Control: Standard

Image Compression: Available: Color: JPEG; Monochrome: G3 and G4
Detect Patch Code: Available through ISIS® driver: Kodak II, III and T

18.5 lbs

Detect Control Sheet: Standard
Detect Double Feed: Standard

External Dimensions: 13.5" W x 11.7" D x 9.4" H

Weight:

Power requirement: AC 100-120V, 50/60Hz

Power Consumption: Scanning: 1A maximum (scanning); 0.3A (standby), 0.1A (sleep)

Operating enviornment: 59° to 86° F; 30% TO 80% RH Storage Enviornment: 55° to 86° F; 30% TO 80% RH

Accessories: Installation, & Maintenance Manuals; CD containing Operation,

Paper Port software CD, RTIV & P.I.E. Manuals; AC power cable,

& Cleaning paper.

Options: Roller exchange kit (KV-SS0022), Roller Cleaning Kit

(KV-SS03), White Roller Kit (KV-SS0023)

Warranty: One year swap / exchange



Preliminary specifications, all information subject to change without prior notification

For your nearest Dearler/Distributer please call 1-800-742-8086

Technical Support: 1-800-PANASYS (800-726-2797)



